

### Callidus CPP+ 380 AM TRX DD EAS system

#### PRODUCT FEATURES

- Network connection, remote tuning and management
- Buzzer and RGB alarm lights
- MQTT and REST API accessible
- Advanced SW features (tag-too-close, adaptive sensitivity adjustment, etc.)
- People counting and alarm validation
- Build-in jamming detection
- Build-in permanent magnet detection
- Build-in booster bag detection
- Optional pager for message transmission
- Transparent or solid version available
- Silver or black colors available
- Different alarm types settings (incoming, outgoing, etc.)
- The system can be set to the energy-saving mode, using a system enable key or programmed schedule, outside store opening hours.
- Easy to use ShopMonitor Lite Dashboard for alarm event management

#### AVAILABLE ACCESSORIES

- AM deactivator
- ShopMonitor Lite Dashboard
- Bumper

#### COMPATIBILITY

- AM 58 kHz tags, labels and accessories

#### MECHANICAL

Width	38.2 cm (15 in)
Height	168 cm (66.1 in)
Thickness	5.5 cm (2.2 in)
Base depth	9.5 cm (3.7 in)
Weight	9.5 kg

#### ELECTRICAL

Power requirement	115V/60Hz or 230V/50Hz, 40W max, 5W standby
Operating frequency	58 kHz
Alarm mode	Buzzer/RGB alarm indicator

#### DETECTION DISTANCE (for DR labels)

up to 110 cm (3.61 ft) - each side
up to 244 cm (8.01 ft) - TRX-TRX aisle
up to 228 cm (7.48 ft) - TRX-RX aisle

#### ENVIRONMENTAL

Ambient temperature	0–35°C (equipment for normal indoor use)
Relative humidity	0–90% (non-condensing)

#### PRODUCT ORDER CODES

CPP+ 380 AM TRX with EU UL PSU	18-501.TPDDABC-EU
with US UL PSU	18-501.TPDDABC-US
with UK UL PSU	18-501.TPDDABC-UK
CPP+ 380 bumper	19-061.38

