

Callidus CPP+ 380 RF TRX EAS system

PRODUCT FEATURES

- Network connection, remote tuning and management
- Buzzer, RGB light alarm, and RGB decoration light
- MQTT and REST API accessible
- Advanced SW features (tag-too-close, jammer detection, adaptive sensitivity adjustment, etc.)
- Alarm validation/directional alarms for aisles
- People counter
- Silver or black variants available
- Optional hard tag detacher detection
- Optional paging messages transmitter

AVAILABLE ACCESSORIES

- RF TRX power supply
- RF deactivator
- Bumper

COMPATIBILITY

- RF 8.2 MHz tags, labels and accessories

MECHANICAL

Width	38.2 cm (15 in)
Height	168 cm (66.1 in)
Thickness	5.5 cm (2.2 in)
Base depth	9.5 cm (3.7 in)
Weight	10.5 kg

ELECTRICAL

Power requirement	48VDC/15W per pedestal
Operating frequency	8.2 MHz
Alarm mode	Buzzer/RGB alarm indicator

DETECTION DISTANCE

for 40x40mm labels	up to 2 x 91 cm (3 ft) - each side
	up to 182 cm (6 ft) - TRX-TRX aisle

ENVIRONMENTAL

Ambient temperature	0–35°C (equipment for normal indoor use)
Relative humidity	0–90% (non-condensing)

PRODUCT ORDER CODES

CPP+ 380 RF TRX, silver	18-512.TPABC
CPP+ 380 RF TRX, black	18-512.TPANC
RF TRX power supply 65W	7351.xx (.EU; .US; .UK; .AUS)
RF TRX power supply 25W	7357.xx (.EU; .US; .UK; .AUS)
CPP+ 380 bumper	19-061.38
System licenses	see RF TRX licenses brochure

