

Callidus CPP+ 300L AM TRX lite EAS system

PRODUCT FEATURES

- Cost-effective AM solution
- Network connection, remote tuning and management
- Buzzer and RGB alarm lights
- Advanced SW features (tag-too-close, adaptive sensitivity adjustment, etc.)
- Easy installation
- TRX (monostand) or TX-RX dual configuration
- Build-in jamming detection
- The system can be set to the energy-saving mode, using a system enable key or programmed schedule, outside store opening hours.
- Possibility to connect Dashboard for alarm event management via network connection

AVAILABLE ACCESSORIES

- Callidus CPP+ 300L AM TRX lite RX - a receiver only for dual configuration
- AM deactivator
- ShopMonitor Lite Dashboard for event management
- Bumper

COMPATIBILITY

- AM 58 kHz tags, labels and accessories

MECHANICAL

Width	30 cm (11.8 in)
Height	153 cm (60.2 in)
Thickness	5.5 cm (2.2 in)
Base depth	10.5 cm (4.1 in)
Weight	TBD

ELECTRICAL

Power requirement	115V/60Hz or 230V/50Hz, 37W max. 2.5 standby
Operating frequency	58 kHz
Alarm mode	Buzzer/RGB alarm indicator

DETECTION DISTANCE

(for DR labels)	220 cm (7.2 ft.) - TRX-TRX configuration 200 cm (6.56 ft.) - TX-RX configuration
-----------------	---

ENVIRONMENTAL

Ambient temperature	0-35°C (equipment for normal indoor use)
Relative humidity	0-90% (non-condensing)

PRODUCT ORDER CODES

CPP+ 300L AM TRX lite with EU UL PSU	18-544.TABC-EU
with US UL PSU	18-544.TABC-US
with UK UL PSU	18-544.TABC-UK
CPP+ 300L AM TRX lite RX	18-544.TRABC
CPP+ 300 bumper	19-061.30



Note: One AM TRX UL external power supply per TX-RX pair.