

Callidus CPP+ 540 AM-RF hybrid LGP EAS system

PRODUCT FEATURES

- Both technologies (AM and RF) in one pedestal
- Network connection, remote tuning and management
- Buzzer and RGB alarm lights
- Advanced SW features (tag-too-close, adaptive sensitivity adjustment, etc.)
- People counting and alarm validation
- Build-in jamming detection
- Silver or black colors available
- Optional foil bag and/or permanent magnet detection
- Different alarm types settings (incoming, outgoing, etc.)
- Easy to use ShopMonitor Lite Dashboard for alarm event management
- Advertisement (LED backlighted panels), panel dimensions: 1395x485 mm, visible area 1395x470 mm, recommended material e.g. RAUCH singJET BackLight 200M - 0.2mm

AVAILABLE ACCESSORIES

- AM/RF S1000 deactivator
- ShopMonitor Lite Dashboard
- External power supplies for backlight panels
- Bumper

COMPATIBILITY

- AM 58 kHz and RF 8.2MHz tags, labels and accessories

MECHANICAL

Width	54.5 cm (21.5 in)
Height	168 cm (66.1 in)
Thickness	5.5 cm (2.2 in)
Base depth	9.5 cm (3.7 in)
Weight	18.5 kg

ELECTRICAL

Power requirement	115V/60Hz or 230V/50Hz, 50W max, inbuild UL power supply External power supply required for backlight panels (not included)
Operating frequency	58 kHz and 8.2 MHz frequency range
Alarm mode	Buzzer/RGB alarm indicator

DETECTION DISTANCE

(for AM DR labels and 40x40mm RF labels)	up to 2x90 cm (3 ft.) - each side up to 180 cm (6 ft.) - aisle
--	---

ENVIRONMENTAL

Ambient temperature	0-35°C (equipment for normal indoor use)
Relative humidity	0-90% (non-condensing)

PRODUCT ORDER CODES

CPP+ 540 AM-RF hybrid LGP silver	18-552.LPUABC
CPP+ 540 AM-RF hybrid LGP black	18-552.LPUANC
LGP power supply	14-900.PSU
AM/RF S1000 deac. control unit	19-081.C
CPP+ 540 bumper	19-061.50
System licenses	see AM TRX licenses brochure

